Interoffice Memo



Hoyd bolett

Originating Office: Seattle Cement Plant

Date: July 14, 1982

T0:

D. H. Armstrong

FROM:

L. L. Coslett

SUBJECT:

PCB Transformers/Circuit Breakers

Attached please find inventory/inspection data sheets on all PCB containing equipment currently in use at the Seattle Cement Plant.

No PCB containing equipment was found to be in storage. Total inventory consists of six units with PCB rating and two units rated PCB contaminated.

LLC/mme Attachments

cc: T. G. Wells

K. J. Rone

P. E. Burton

R. J. Rajki

USEPA SF 1261048

١.	Name of Lone Star facility Seattle Cement Plant
2.	Location of PCB equipment Main floor Finish Mill Building - West
3.	Leaks observedNone
4.	Service or replacement of transformer Unit in use and found to be in good working condition.
5.	Other observations G.E. Analysis - Greater than 50% PCB (Pyronol)
6.	Estimated weight of PCB in kilograms*. assume a. PCB in use 180 gal. x 6 kg/gal x 100% = 1080 kg.
	b. PCB in storage None kg.
	c. PCB to disposal None kg.
7.	(Location of disposal site) Name of inspector Paul E. Burton - Electrical Foreman Date 7-13-82 Lloyd L. Coslett - Safety Coordinator 7-13-82
	EQUIPMENT IDENTIFICATION General Electric Low Voltage Power Circuit Breaker No. 179A5066-784AD - Type AK-2-50-3 - S/N 963295A, 1600 Amp - 3Ø - 60 HZ - 180 gal. capacity (600 VAC - 42,000A - 480 VAC - 50,000A) (240 VAC - 65,000A - 250 VAC - 50,000A)

^{*}Weight=gallons x 6 Kilograms/gallon x Percent concentration of PCB.

1.	Name of Lone Star facility Seattle Cement Plant	
2.	Location of PCB equipment Main floor Finish Mill Buildi	ing - East
3.	Leaks observed None	
4.	Service or replacement of transformer <u>Unit in use and</u> good working condition.	d found to be in
5.	Other observations <u>G.E. Analysis</u> - Greater than 50% PCB ((Pyronol)
6.	Estimated weight of PCB in kilograms*. assume a. PCB in use 180 gal. x 6 kg/gal x 100% = 1080 kg.	
	b. PCB in storage None kg.	
	c. PCB to disposal None kg. (Location of disposal site	,
7.	David C Dunton Clastical Commun	Date 7-13-82
	EQUIPMENT IDENTIFICATION General Electric Low Voltage Power Circuit Breaker No. 179A Type AK-2-50-3 - S/N F963295B, 1600 Amp - 3Ø - 60 HZ - 180 (600 VAC - 42,000A - 480 VAC - 50,000A) (240 VAC - 65,000A - 250 VAC - 50,000A)	

^{*}Weight=gallons x 6 Kilograms/gallon x Percent concentration of PCB.

Name of Lone Star	facility Seatt	le Cement Plant	·-···
Location of PCB eq	uipment Group 2 Cen	ment Storage Silos	
Leaks observed	None		
Service or replace		. Unit in use and found	to be in
Other observations	G.E. Analysis - Grea	ter than 50% PCB (Pyrono	1)
	of PCB in kilograms* assur 5 gal x 6 kg/gal x 100	me	
b. PCB in storage	None	kg.	
c. PCB to disposa	None	kg.	
(Location of d	disposal site		
	Paul E. Burton - Elec	trical ForemanDate	7-13-82
Name of inspector_	Lloyd L. Coslett - Sa	fety Coordinator	7-13-82

General Electric Transformer - S/N F-963361, Class OA/FA 3Ø 60 HZ - Voltage Rating 4160/480/277 - 750 KVA - Cont. $65^{\rm O}$ C Rise Self Cooled Al3B3B - 135 gal. capacity

^{*}Weight=gallons x 6 Kilograms/gallon x Percent concentration of PCB.

						e Cement				_
Loca	tion	of PCB e	quipme	entC	linker Stor	age Silo	s			
Leak	s ob	served	None					 		
		or replac working co				Unit in		found	to t	96
Othe		servation Analysis								
a .	PCB	in use	of PCE 140 gal	3 in ki` .x6 kg/	lograms* assu /gal x 100	me 1% = 840	kg.			
a .	P C B	in use	140 gal	. x 6 kg/	/gal x 100	840				
a. b.	PCB PCB	in use	140 gal e	. x 6 kg/	/gal x 100 None	% = 840 	kg.			
a. b.	PCB PCB	in use	140 gal e	. x 6 kg/	/gal x 100 None None	% = 840 	kg. kg.			

^{*}Weight=gallons x 6 Kilograms/gallon x Percent concentration of PCB.

				i ty						
Loc	ation	of PCB	equipme	ntSlurr	y Tanks	Substati	on			
Lea	ks ob	served_	None							
		or repl		of trans		Unit i				
Oth	er ob	servati	ons			· —				
		-								
							_			
Est	imate	d weigh	t of PCB	3 in kilo	grams*.					
		•		3 in kilo x 6 kg/gal	_		<u>84</u> kg.	*		
a.	P C B	in use	981 gal.		x 507 P		84_kg. kg.	*		
a. b.	PCB PC8	in use	981 gal.	x 6 kg/gal	x 507 P		kg.	*		
a. b.	PCB PCB	in use in stor	981 gal. age	x 6 kg/gal	x 507 P	PM = 2.9	kg.			
a. b.	PCB PCB Loc	in use in stor to disp	981 gal. age osal f dispos	x 6 kg/gal None None	x 507 P	PM = 2.9	kg.		7-13-8	2

EQUIPMENT IDENTIFICATION

Westinghouse 3750/4200 KVA - 3Ø - 60 HZ - 2400V - S/N PCR61541 981 gallon capacity - Transformer Consultants (TC) Tag #13.

^{*}Weight=gallons x 6 Kilograms/gallon x Percent concentration of PCB.

	Name of Lone Star facility Seattle Cement Plant
	Location of PCB equipment Incoming Power Substation (Owned by Seattle City Ligh
•	Leaks observed None
•	Service or replacement of transformer Unit in use and found to be in excellent condition.
	Other observations
	Estimated weight of PCB in kilograms*. a. PCB in use 30 gal. x 6 kg/gal x 646 PPM = 0.116 kg. *
	b. PCB in storage None kg.
	c. PCB to disposal None kg.
	(Location of disposal site)
•	Name of inspector Paul E. Burton - Electrical Foreman Date 7-13-82 Lloyd L. Coslett - Safety Coordinator 7-13-82
	EQUIPMENT IDENTIFICATION Seperal Flectric 75KVA - 4160V - 30 - 60 H7 S/N H2216538-68P

*Weight=gallons x 6 Kilograms/gallon x Percent concentration of PCB.

40 Amp. - 30 gallon capacity - Transformer Consultants (TC) Tag #12.

1.	Name of Lone Star facility Seattle Cement Plant		
2.	Location of PCB equipment No. 1 Kiln under No. 3 Pier		
3.	Leaks observed None		
4.	Service or replacement of transformer Unit in use good working order.		<u>n</u>
5.	Other observations		
	PCB contaminated.		
6.	Estimated weight of PCB in kilograms*.		
	a. PCB in use 20 gal x 6 kg/gal x 92 PPM = 0.011 kg.	*	
	b. PCB in storage None kg.		
	c. PCB to disposal None kg.		
7.	(Location of disposal site		
	EQUIPMENT IDENTIFICATION Name Plate Missing - 20 gallon capacity. Transformer Consultants (TC) Tag #33.		

^{*}Weight=gallons x 6 Kilograms/gallon x Percent concentration of PCB.

1.	Name of Lone Star facility Seattle Cement Plant
2.	Location of PCB equipment <u>Electrostatic Precipitator - Section #3</u>
3.	Leaks observed None
4.	Service or replacement of transformer Unit in use and found to be in
	good working order.
5.	Other observations
	PCB contaminated.
6.	Estimated weight of PCB in kilograms*.
	a. PCB in use 155 gal. x 6 kg/gal. x 119 PPM= 0.111 kg. *
	b. PCB in storagekg.
	c. PCB to disposal None kg.
	(Location of disposal site
7.	
•	Lloyd L. Coslett - Safety Coordinator 7-13-82
	EQUIPMENT IDENTIFICATION
	General Electric - 55 KV - D.C 600 Amp - 10 - 60 HZ

^{*}Weight=gallons x 6 Kilograms/gallon x Percent concentration of PCB.